

IN THIS ISSUE

Alternators	3	Fuse Holders	6	Toolbox Canopies	11
Battery Chargers	5	Kits	6	Tools & Tool Kits	11
Battery Monitors	5	Low-Voltage Disconnects	5	Tyre Pressure Units	10
Charge Controllers	5	Recovery Accessories	8-10	Work Lights	4
Connectors	6	Starters	2-3		
Converters	5	TE Connectors	7		


Brand names and descriptions are for reference purposes only | E&OE

NORDICLIGHTS

**Scorpius Blue 400
Crop-Sprayer Spot Light**
• 12 - 24 V
• 42 w
• For Agricultural Markets

Key Features

- Optimised illumination of boom and spray pattern
- Light colour: blue, 475 nm
- Superior electromagnetic compatibility (CISPR 25 Class 5)



T984-801B



NOCO
Since 1914

**T120016915
GB40**

**1 000
Amp**

GB40 BOOST PLUS Lithium Jump Starter


- 12V
- 24 Watt-hour Internal Lithium Battery
- Features Spark-Proof Technology and Reverse-Polarity Protection
- Instantly Jump Starts most Single-Battery Applications up to **20x** on Single Charge
- Compatible with Engines up to 6 l Petrol & 3 l Diesel
- 1.08 kg



Ultra Safe,
Ultra Compact
& Portable

196 x 80.3 x 43.4 mm

**MITSUBISHI
ELECTRIC**
Changes for the Better



100% Genuine
Mitsubishi Electric
Automotive Parts

Trysome is the
official distributor
for **Mitsubishi
Electric** in Africa.

Please contact our sales representatives for an official quotation at online.purchases@trysome.cc.

0861 879 766

DELIVERING OPTIMAL UPTIME!



TERMS & CONDITIONS OF SALE

WARRANTY STATEMENT

Trysome warrants that all products will be covered for manufacturing faults. Trysome's warranty does not, however, extend to rectifiers, regulators, globes, fuses or diodes.

All products supplied by Trysome, are supplied and provided on the condition that we cannot be held responsible in the event that they are used for any other purpose than that specified by the manufacturer. Trysome's warranty, therefore, does not cover misuse, abuse, incorrect fitment or applications.

The customer or purchaser accepts that it is their responsibility to ensure that the product is used in accordance with the manufacturer's instructions.

The commencement date of all warranties is the date of invoice to the purchaser, unless otherwise agreed by Trysome in writing.

SERVICE

Trysome has its own service department with qualified technicians so that, unlike many wholesalers, we are able to provide you, our Customer, with a complete after-sales service.

Note:

- Trysome Auto Electrical Engineering (Pty) Ltd reserves the right to change terms, conditions, and specifications shown in this catalogue at any time.
- Some names and part numbers are used for reference purposes only.
- Some of our products are manufactured to order so please allow lead times.
- The information contained herein is deemed to be correct at the time of going to print, but Trysome assumes no liability for typographical errors or omissions.
- Copyright 2024 by Trysome Auto Electrical Engineering (Pty) Ltd. All rights reserved.
- E&OE

Trysome Auto Electrical Engineering (Pty) Ltd is the authorised distributor of the brands it markets.

For bulk discounts on
premium brands contact:
Dawid.Boshoff@trysome.cc



AUTOCOMM

ROTATING EQUIPMENT

STARTERS



**Delco-Type
39MT Starter**

- **12 V**
- 11 Tooth
- 7.5 kW
- Rotatable Flange



T011003689B
8200308
STR2127



**Delco-Type
28MT Starter**

- **12 V**
- 12 Tooth
- Dry Clutch
- 46.5 mm Pinion
- Left-Hand Open
- Bobcat/
Perkins



GP ONLY

T011103659
1113273
STR2680



**Delco-Type
39MT Starter**

- **24 V**
- 11 Tooth
- 8.3 kW
- Rotatable Flange




T011003687B
8200321
STR2696

fabbro

**Prestolite-Type
M100R Starter**

- **12 V**
- 10 Tooth
- 4.0 kW
- Deutz



GP ONLY

T010019700
M100R2004SE
STR9727

fabbro

**Bosch-Type
EV Starter**

- **24 V**
- 9 Tooth
- 4.0 kW
- Long Nose
- MB OM356,
OM357, &
OM366 Engines




GP & KZN

T0104036148B
0001231003
STR1175

fabbro

**Bosch-Type
EV Starter**

- **24 V**
- 11 Tooth
- 4.0 kW
- DAF



T0104036135B
0001231013
STR1244

Please contact our sales representatives for an



STARTERS

Delco Remy **BorgWarner** **T011103611DR**
10461052 STR2617

42MT Starter
• 12V
• 11 Tooth
• 7.3 kW
• Direct Drive
• PMGR
• Factory Remanufactured
GP ONLY



Delco Remy **BorgWarner** **T011103646**
10478998 STR2642

42MT Starter
• 24V
• 11 Tooth
• 8.0 kW
• Direct Drive
• CAT, Cummins, ERF



Delco Remy **BorgWarner** **T011003687**
8200330 STR2696

39MT Starter
• 24V
• 11 Tooth
• 8.3 kW
• Rotatable Flange



360° 3D **IMS** **OCP**
INTEGRATED MAGNETIC SWITCH OVERCRANK PROTECTION

Delco Remy **BorgWarner** **T011003650**
10479339P STR2652


50MT Starter
• 24V
• 11 Tooth
• 9.0 kW
• Direct Drive



Trysome is a proud distributor of...

C.E. Niehoff & Co.
CHARGING AND POWER MANAGEMENT SYSTEMS

- Heavy-Duty Brushless
- Reduced EMI
- High Efficiency
- Long-Life Bearings
- Air Cooled
- Field Serviceable
- Multiple Mounting Options
- High Output at Low Idle Speed
- 14 V to 700 V
- 60 to 960 Amp Output




Generous Air Flow
Laminated Paths
Robust Design
Stationary Windings
Minimal Moving Parts
Long-Life Bearings
Winding Flexibility

ALTERNATORS


WAI **T020403696**
0120488185 ALT1170

Bosch-Type K1 Alternator
• 12V
• 55 Amp
• Left Hand
• No Pulley
• Deutz/KHD
GP, NW & KZN




WAI **T021009217**
0120468143 ALT1030

Bosch-Type NL1 Alternator
• 24V
• 100 Amp
• Actros/Atego/Citaro




WAI **T020409209IMP**
0120469585 ALT1173

Bosch-Type N1 Alternator
• 24V
• 55 Amp
• 56 mm Double Foot
• Deutz/KHD/Liebherr/Powerstar



WAI **T022803605**
1002114100 ALT6039

Nippon Denso-Type Alternator
• 24V
• 20 Amp
• 2 Pin (L-G)
• Toyota Forklift/1Z Engine



Leece-Neville **T022303626**
8TA2031G ALT9715

Alternator
• 12V
• 45 Amp
• 50 mm Single Foot
• Enclosed
GP ONLY




Leece-Neville **T022303634**
BLP2310 ALT9722

Alternator
• 12V
• 160 Amp
• Pad Mount
• International/Mack/Volvo



Delco Remy **BorgWarner** **T021009295**
8600764 ALT2639

28SI Alternator
• 24V
• 100 Amp
• 5 Pin (W-L-IG-S-DFM)
• Mercedes-Benz



Delco Remy **BorgWarner** **T021009297**
61000853 ALT9735 similar

40SI Alternator
• 24V
• 160 Amp
• J180 Mount
• International Truck Engines
• Volvo/CAT/Freightliner



Delco Remy **BorgWarner**

BorgWarner's acquisition of Remy International brings two leading companies together to deliver even more value to our customers.



WORK LIGHTS

NORDICLIGHTS

T982-601B

KL2001 LED Work Light Wide Flood Beam

- 12 - 24 V
- 20 w
- Built-in Deutsch Plug
- Top-Top Pedestal



IP68
IP6K9K



94 x 104 x 59 mm

NORDICLIGHTS

T982-801B/802B

KL1401 LED Work Lights Wide or Flood Beam

- 12 - 24 V
- 42 w
- Built-in Deutsch Plug
- Top-Top Pedestal



110 x 110 x 74 mm

NORDICLIGHTS

T988-203B

Scorpius Go 420 LED Work Light Flood Beam

- 12-24 V
- 28 w
- Built-in Deutsch Plug
- 9 LEDs
- 2 200 Lumens
- Top-Top Pedestal



IP68
IP6K9K



118 x 99 x 66 mm

NORDICLIGHTS

T989-101B

Scorpius Pro 415 PH Anti-Glare Work Light Wide Flood Beam

- 12 - 24 V
- 28 w
- Built-in Deutsch Plug
- 1 500 Lumens
- 5 000 K

No More Blinding Glare... with Nordic's 3-in-1 Optical Solution!

With these work lights mounted on your heavy-duty vehicle you will have accent lighting with soft illumination directed upwards as a guide light for successful lifting and other operations. You will also have efficient task lighting to illuminate the work area both directly in front of and further from the vehicle. For instance, mounted on a forklift truck, the Phenom Optics solution also directs light onto the forks, which is not the case with standard work lights. The third and most brilliant part of the optical solution is the glare-free zone created by the clear horizontal cut-off line, ensuring that people and other vehicles working nearby will not be blinded.



100 x 100 x 86 mm

ACCENT LIGHTING

Soft illumination upwards as a guide light for successful lifting operations

GLARE-FREE ZONE

Will not blind people working in the vicinity of the vehicle

TASK LIGHTING

Effectively illuminating the work area



IP68
IP6K9K

ICONIQ

Classic Engineering

T650019731

LED Work Light Flood Beam

- 10 - 30 V
- 27 w
- 9 LEDs
- 2 200 Lumens
- Aluminium Body



IP67

135 x 117 x 46 mm

ICONIQ

Classic Engineering

T720019727

LED Work Light Flood Beam

- 9 - 32 V
- 42 w
- 2 700 Lumens
- E9 Certification



IP67

117 x 70 x 128 mm

No more welding or drilling on your expensive assets!



Click Bond Adhesive-Bonded Fastener Technology...

- > Enhances Structural Strength and Integrity
- > Streamlines Manufacturing
- > Facilitates Repair



Please contact our sales representatives for an



BATTERY MONITORS

CTEK MAXIMIZING BATTERY PERFORMANCE

Battery Sense Smart Battery Health Monitor

- Easily track the health of your vehicle battery with this unique Bluetooth-enabled smart track device.
- It is easy to install, and data is delivered through a free-to-download iPhone or Android app.
- Provides valuable information about your vehicle's battery in a simple, user-friendly way.
- Continuously measure the battery to provide information about its health.



T26001561297
CTXB



victron energy BLUE POWER

T120014800
BAM030712000R

BMV-712 Smart Battery Monitor

- 6.5-70 Vdc
- Easy to Install
- Midpoint Voltage Monitoring
- Very Low Current Draw from the Battery
- Bi-stable Alarm Relay
- Bluetooth Smart



IP65s



69 mm

CONVERTERS

alfatronix POWER, NO COMPROMISE

T286512803
PV24S

Voltage Converter

- **24 - 12 V**
- 24/30 Amp
- 288 w
- Non-Isolated
- 620 g



IP65

168 x 87 x 50 mm

victron energy BLUE POWER

T2810517500
ORI242410110

Orion-Tr DC/DC Converter

- **24/24 V**
- **5 Amp**
- 120 w
- Isolated



victron energy BLUE POWER

T129616902
SCC010020020



BlueSolar PWM-Light Charge Controller

- **12/24 V** Automatic System Voltage Detection
- **20 Amp** Current Charge
- Automatic Load Disconnect

IP20

45 x 81 x 182 mm

CHARGE CONTROLLER

LOW-VOLTAGE DISCONNECTS

Whether you are involved in the automotive or marine markets, or are specifying original-fit components at OEM level, we have a wide range of products to suit your needs!



alfatronix POWER, NO COMPROMISE

alfatronix POWER, NO COMPROMISE

T286512828
PT60

Low-Voltage Disconnect

- Input **9-32 Vdc** (Automatic Referencing)
- **60 Amp**
- 155 g



IP65

76 x 78 x 33 mm

alfatronix POWER, NO COMPROMISE

T286512830
PT200

Low-Voltage Disconnect

- Input **9-32 Vdc** (Automatic Referencing)
- **200 Amp**
- 530 g



IP65

124 x 97 x 51 mm

BATTERY CHARGERS

victron energy BLUE POWER

T750020032
BPC120731064R

Blue Smart Battery Charger

- **12 V** Input
- 230 V Output
- **7 Amp**
- CEE 7/17
- 7-Step Smart Charge Algorithm
- **1 Outlet**



IP65



47 x 95 x 190 mm

victron energy BLUE POWER

Orion-TR Smart 12/12-30A (360 w) Non-isolated DC-DC Charger

- Bluetooth Smart Enabled
- Fully Programmable
- Adaptive 3-Stage Charge Algorithm: Bulk, Absorption, & Float
- Remote On-Off
- Screw Terminals
- All Models are Short-Circuit Proof and can be Paralleled to Increase Output Current
- High-Temperature Protected
- Input Fuse (Not Replaceable)



takealot

IP43

130 x 186 x 80 mm

T120016940
ORI121236140



ELECTRICAL HARNESSING & COMPONENTS

KITS

VISIT OUR WEBSITE
for full contents lists

TFlex

T420003800

471
Pieces



Heat Shrink Tube Kit


- Mix of Colours
- 50/100/160 mm



TFlex

T420003801

182
Pieces



Heat Shrink Tube Kit

- Mix of Colours
- 160 mm



TFlex

T420010616

86
Pieces



Heat Shrink Tube Kit

- Black
- 100 mm



TFlex

T2600038114

144
Pieces



18-Part Amp Superseal Kit

- 1.5 Series
- Temperature Range: -40 °C to +125 °C



TFlex

T440008639

1 475
Pieces




24-Part Contractor's Copper Lug & Ferrule Kit



TFlex

T410003800

2 050
Pieces



Terminal Kit

- Single Grip
- No Crimper
- 24 Different Terminals



CONNECTORS

FUSE HOLDERS



T440008617

603
Pieces



Deutsch DT Series Large Connector Kit

- No Crimper
- Environmentally-Sealed Transportation Connectors



T135110011

724800



Midi Bolt-Down Fuse Holder

- 30-200 Amp
- Small



T135110010

824800



Mega Bolt-Down Fuse Holder

- 80-500 Amp



Deutsch Terminal-Release Tool Kit

Widely used for vehicles, trucks, and equipment with German terminal connectors, such as Caterpillar, Peter Bildt, cargo fleet, construction, & agricultural machinery.



Deutsch Solid Crimper Kit

Crimping tool for wire connectors, with precise ratchet structure and ergonomic handle that make the crimp firm and tight. The quick-release lever feature means that anyone can easily master it. It is a general-purpose tool for all wiring projects.



Please contact our sales representatives for an



In heavy industries, electrical systems must stand up to rigorous conditions and all weather environments. Failure in an electrical system can be expensive to diagnose, and downed equipment can stop entire operations. As equipment becomes increasingly sophisticated and reliant on electronic packaging and diagnostics, design engineers know the importance of choosing environmentally sealed electrical connectors capable of holding up to extreme conditions.

Many manufacturers count on **TE Connectivity's** electrical connectors to maintain their electrical connections. Their Deutsch Connectors are a series of environmentally sealed connectors that are designed for use in harsh environments where field serviceability is essential.

TE Connectivity Connectors offer different shapes, latching mechanisms, mounting styles, and materials to meet diverse application requirements and offer accessories to further expand the series' flexibility. Below is an overview of each connector series that highlights the cavity count, wire gauge, material, and locking mechanism style.

DRC SERIES



- Accepts contact sizes 16 (13 amps), and 20 (7.5 amps)
- 14-22 AWG (2.50-0.35 mm²)
- 24, 40, 50, 60, 64, 70, and 80 cavity arrangements
- In-line, flange, or PCB mount
- Rectangular, thermoplastic housing
- Jackscrew for mating

DT SERIES



- Accepts contact size 16 (13 amps)
- 14-20 AWG (2.5-0.50 mm²)
- 2, 3, 4, 6, 8, and 12 cavity arrangements
- In-line, flange, or PCB mount
- Rectangular, thermoplastic housing
- Integrated latch for mating
- Wedgelocks confirm contact alignment and retention

DTHD SERIES



- Accepts contact sizes 4 (100 amps), 8 (60 amps), and 12 (25 amps)
- 6-14 AWG (16.00-2.00 mm²)
- 1 cavity arrangement
- In-line or flange mount
- Circular, thermoplastic housing
- Integrated latch for mating

DTM SERIES



- Accepts contact size 20 (7.5 amps)
- 16-22 AWG (2.50-0.35 mm²)
- 2, 3, 4, 6, 8, and 12 cavity arrangements
- In-line, flange, or PCB mount
- Rectangular, thermoplastic housing
- Integrated latch for mating
- Wedgelocks confirm contact alignment and retention

DTP SERIES



- Accepts contact size 12 (25 amps)
- 10-14 AWG (6.00-2.00 mm²)
- 2 and 4 cavity arrangements
- In-line, flange, or PCB mount
- Rectangular, thermoplastic housing
- Integrated latch for mating
- Wedgelocks confirm contact alignment and retention

HD10 SERIES



- Accepts contact sizes 4 (100 amps), 12 (25 amps), and 16 (13 amps)
- 6-20 AWG (16.00-0.50 mm²)
- 3, 4, 5, 6, and 9 cavity arrangements
- In-line, flange, or PCB mount
- Circular, thermoplastic housing
- Coupling ring for mating

HD30 SERIES



- Accepts contact sizes 4 (100 amps), 8 (60 amps), 12 (25 amps), 16 (13 amps), and 20 (7.5 amps)
- 6-22 AWG (13.00-0.35 mm²)
- 2, 6, 8, 9, 14, 16, 18, 19, 20, 21, 23, 29, 31, 33, 35, and 47 cavity arrangements
- In-line or flange mount
- Circular, aluminium housing
- Coupling ring for mating

HDP20 SERIES



- Accepts contact sizes 4 (100 amps), 8 (60 amps), 12 (25 amps), 16 (13 amps), and 20 (7.5 amps)
- 4-22 AWG (25.00-0.35 mm²)
- 2, 6, 7, 8, 9, 14, 16, 18, 19, 20, 21, 23, 29, 31, 33, 35, and 47 cavity arrangements
- In-line or flange mount
- Circular, thermoplastic housing
- Coupling ring for mating





ADVENTURE PRODUCTS & ACCESSORIES

RECOVERY ACCESSORIES



T2200156217
SBR-12KRR

Bag
Included



NEW

9 m



12K Kinetic Recovery Rope

- 12 500 kg Maximum Breaking Strength
- Flexible and Heavy-duty Nylon 66 Material



T2200156194
SBR-8KRR



9 m

Bag
Included



Heavy-Duty Kinetic Recovery Rope

- 8 000 kg Breaking Strength
- Soft yet Durable Vinyl
- Polymer-Coated Eyes for Extra Rope Protection
- Flexible & Heavy-Duty Nylon 66 Material



T2200156193
SBR-30DBSWR



30 m

Bag
Included



Spectra Extreme Double-Braided Winch Rope

- Minimum Breaking Strength of 8 000 kg
- Double Braided with Our Exclusive SaberPro™ Fibre. Offering the Highest Standards in Strength and Durability. It Won't Let You Down!



T2200156199
SBR-15SEUR



Bag
Included



Spectra® Extreme Utility Rope

- Ranked at 15 000 kg Minimum Breaking Strength
- Includes Sheath to Protect Trees



T2200156195
SBR-14KBSS



Bag
Included



Soft Shackle with Protective Sheath

- 11 mm Soft Shackle with Protective Sheath
- 14 700 kg Minimum Breaking Strength
- Abrasive-Resistant Protective Sheath



T2200156196
SBR-14KSS



SaberPro™ Bound Soft Shackle

- 11 mm x 0.52 mm Soft Shackle
- 17 000 kg Breaking-Strain Strength
- Uniquely Bound High Abrasion and Impact-Resistant UHMWPE (Ultra High Molecular Weight Polyethylene) Material



T2200157000
SBR-10KBSSB



Bag
Included



HDX Technora-Bound Soft Shackle

- 10 000 kg Breaking Strength
- Technora Cut-Resistant Binding
- Constructed from SaberPro™ Fibre
- Can be used in a Wide Range of Applications



T2200156197
SBR-9KSS



Double-Braided Soft Shackle

- 9 000 kg Breaking Strength
- High Abrasion and Impact Resistance
- Can be used in a Wide Range of Applications



T2200156200
SBR-15KRR



Bag
Included



Ezy-Glide Recovery Ring

- Designed with T6 Billet Aluminium, Exceeding the Working Load Limit (W.L.L) of 12 000 kg
- Internal Channel Designed for Synthetic Winch Ropes of ≤10 mm



T2200156216
SBR-4KRR



9 m



4K Kinetic Recovery Rope

- 4 000 kg Breaking Strength
- Includes Bag
- Flexible & Heavy-Duty Nylon 66 Material



T2200157003
SBR-RGB1



Recovery-Gear Bag

- Manufactured with Heavyweight Ripstop PVC and Load-Tested Saber Webbing
- Heavy-duty Zips and Double Slider
- Internal Pockets

Please contact our sales representatives for an



RECOVERY ACCESSORIES



T2200157005
SBR-GLV1



Utility Gloves

- Designed to Give Support & Protection when Needed Most
- Hard-Wearing
- Extensively Tested Off-Road



T2200158240
BL250




Bumper Lift

- Designed to Fit Most Curved-Steel Bumpers
- Heavy-Duty, All-Steel Construction for Long Life and Durability
- Capacity: 1 361 kg
- Quick and Easy to Use



T2200158411
HL485



48-inch All-Cast Jack

- All-Cast Construction
- 175 kg Tested Capacity
- Most Durable Design

The Only Jack with a 2-Piece Handle and Socket Design that is Built for Extended Life.



T2200158412
HL605



60-inch All-Cast Jack

- All-Cast Construction
- 75 kg Tested Capacity
- Most Durable Design



T2200158415
LM100



Jack Lift-Mate

- Lift Capacity 2 273 kg
- Rubber-Coated Hooks to Protect the Wheel
- Rubber Pad for Protecting the Tyre and Wheel



Kinetic Recovery Rope

Upgrade to the latest Kinetic Recovery Rope from **SABER OFFROAD**. With 50% more stretch than a snatch strap, **kinetic ropes are the way to go!**

Where traditional snatch straps often give less stretch, these **SABER OFFROAD KINETIC RECOVERY ROPES** make a huge difference when it comes to strain on the vehicles, smoothness of the recovery, and safety for those in the immediate vicinity.



T2200158413
HK-R




Handle-Keeper

- Fits all Models of Hi-Lift® Jacks



T2200158414
ORB100



Off-Road Base

- Use the Hi-Lift® Off-Road Base to Alleviate Jack Sinkage on Soft Ground
- Rugged Construction
- Can be Used with Standard Hi-Lift® Jack Models.



T2200158239
FK-1



Fix-It-Kit

Keep your Hi-Lift® Jack operating trouble-free. The **Fix-It-Kit** includes parts for servicing all Hi-Lift® Jack lifting units.



REFRIGERATION



T37001521141



42 L Leisure Series Fridge Freezer

- 12/24 Vac
- 220 Vac
- Temp. Range: -18° C to 10° C
- Lightweight, Compact, & Energy-Efficient
- Digital Temperature Control

445 x 720 x 414.5 mm



1 200 - 2 000 kg
Vehicle Weight

4K KINETIC ROPE



2 500 - 4 000 kg
Vehicle Weight

8K KINETIC ROPE



4 000 - 6 000 kg
Vehicle Weight

12K KINETIC ROPE



5 300 - 8 000 kg
Vehicle Weight

16K KINETIC ROPE



7 800 - 11 000 kg
Vehicle Weight

22K KINETIC ROPE





ADVENTURE PRODUCTS & ACCESSORIES

RECOVERY ACCESSORIES




2-Hose Tyre Pressure Unit

- Rapidly deflates 2 tyres simultaneously, using our patented pressure-release technology
- Inflates 2 tyres simultaneously from your air source
- Automatically equalises both connected tyres' pressure
- Highly accurate gauge for convenient monitoring whilst inflating or deflating



T2200158574



Bag Included



T2200158578

Spare-Wheel Valve Extension

A simple solution for accessing your spare-wheel valve to check or adjust pressure.

The spare-wheel valve extension comes with a small mounting plate that can be connected onto your tow bar, trailer plug, or most other fittings, and comes with a 1.7 m hose.



T2200158579

Hook

The Indeflate Hook is designed to be used with the Indeflate and the Indeflate 4 Hose Unit.

It allows you to hook your Indeflate almost anywhere on your vehicle, so you can deflate or inflate hands-free.



Proven Quality

Manufactured in South Africa, Indeflate has been tried and tested to withstand the forces of nature and last the toughest of overlanding excursions.



QUICK, EASY, & ACCURATE

TRYLECHD

RED SERIES

Energizer



Premium Maintenance-Free Battery Range

Maximum power, every time!

When reliability is everything you need to get going quickly our batteries are perfect. Whether it's for trucks, buses, agriculture or construction vehicles, the ultra stable, impact-proof polypropylene casing and high performance specifications are specially designed to meet high endurance demands.

Key Advantages:

- Silver Calcium
- Fully sealed maintenance-free (reduces costs and risks)
- Ultra longer service life
- Massive cranking power
- Extreme cycle endurance
- Best in class against spill and leakage
- Optimised power for guaranteed starting in all temperatures
- Outstanding recharge acceptance
- Highest vibration resistance - V3 rating
- Labyrinth safety lid with central degassing
- Integral flame arrestors



Please contact our sales representatives for an



KRAFTWERK
FAVORITE TOOLS SINCE 1979

200-Piece Basic Socket Set

- 1/4 inch + 3/8 inch + 1/2 inch socket spanner set
- Fittings 1/4 inch from 4 to 14 mm, socket wrench 3/8 inch from 10 to 19 mm, 1/2 inch from 10 to 32 mm
- Adapters and extensions
- 1/4 inch, 3/8 inch + 1/2 inch socket spanner



T204.104.800

200
PCS

190 x 340 x 75 mm

KRAFTWERK
FAVORITE TOOLS SINCE 1979

T4022

Open Socket Wrench Set

- 19-34 mm
- Includes Ratchet

13
PCS



30 mm



380 x 210 x 55 mm

KRAFTWERK
FAVORITE TOOLS SINCE 1979

T2907-4917

309
PCS



7-Drawer Tool Trolley

- With bearing-guided, single-locking, full pull-out drawers
- With central locking
- With professional tools embedded in high-density soft foam (EVA)
- Coated with a permanent, hard-plastic surface for easy cleaning
- **Tools included**
- 71.7 kg



STOCK
CLEARANCE

695 x 475 x 885 mm

KRAFTWERK
FAVORITE TOOLS SINCE 1979

T3403-54

Flexible Combo Ratchet Spanner Set

- 8-19 mm
- 180° flexible ring head
- Lifetime warranty

12
PCS




325 x 185 x 56 mm

KRAFTWERK
FAVORITE TOOLS SINCE 1979

T4223-400

Water Pump Pliers

- 400 mm
- High-tech Adjustable Clamp




NEW ARRIVALS!

Stainless-Steel Toolbox Canopies

SAFE • SECURE • STYLISH • PRACTICAL • HIGHLY DURABLE

Internal
Set-up
Custo-
misable

Standard Accessories:



25 l Stainless-steel
Water Tank with
External Tap



Shocks on Internal
Flap



Heavy-Duty Push
Locks (Keyed Alike)



Internal 8-Drawer
Toolbox



Heavy-Duty Drawer
Slides



Powder-Coated
Doors and Drawers

Optional Extras:

- Interior Lighting
- Inverter
- Rear Spot Light
- Dual-Battery System
- Kraftwerk Tools
- Mine-Light Bracket
- Tailgate Cover & Vice

Supplied, assembled, & installed within 14 Days!

KRAFTWERK
FAVORITE TOOLS SINCE 1979

T3237

3/4" Torque Wrench

- With window scale for values in Nm and ft.lbs
- Instantly reversible 45-tooth ratchet head
- Hardened steel casing
- Ergonomic 2-component handle with adjustable locking knob
- Certified precision $\pm 4\%$



1 040 mm

GUIDING THE WAY TO INFINITE POSSIBILITIES...

Automation & Control Solutions for Surface Mining.



RCT's **ControlMaster**® solutions are setting the benchmark for productivity and safety on a global scale, empowering clients to improve efficiencies and effortlessly meet production targets.

The **ControlMaster**® automation and control range is versatile enough to cater to specific requirements, ranging from the automation of a single machine to a fully autonomous fleet and beyond.

The **ControlMaster**® range is fully scalable, permitting upgrades from a Line-of-Sight solution to a fully autonomous fleet. In addition, RCT's automation path allows the combination of all the latest technology available to deliver complete solutions, including automation, traffic management, integration and much more.

Proven Technology - no lost-time injuries and the longest operating hours in the market!

These products may not be a stock items. Please speak to our sales representative about lead times. Lead times, price, and availability can only be determined on receipt of an official quote from our supplier. This can sometimes take up to 3 days.

Gauteng - Jet Park (HQ):

T: +27 (0)11 823 5650

Free State - Bloemfontein:

T: +27 (0)63 257 0505

Eastern Cape - Port Elizabeth:

T: +27 (0)82 450 6596

KwaZulu Natal - Pinetown:

T: +27 (0)31 303 4129

Mpumalanga - Middelburg:

T: +27 (0)13 692 8132

Northern Cape - Kathu:

T: +27 (0)53 723 3415

North West - Rustenburg:

T: +27 (0)14 596 5257

North West - Rustenburg:

T: +27 (0)14 596 5257

Botswana, Gaborone:

T: +267 399 4150

Botswana, Letlhakane:

T: +267 297 8568

Mozambique, Tete:

T: +258 252 20666

Zambia, Kitwe:

T: +26 (0)21 222 5338



SCAN HERE to subscribe and receive our latest product news.

Follow us...



trading@trysome.co.za • www.trysome.co.za • PO Box 13677, Witfield 1467




- Increased Run Time
- More Buckets
- Reduce Machine Damage
- Eliminate Unplanned Downtime
- Less Wear and Tear
- Fuel Efficiency

Profit



- Operator Health
- Easy-to-Use
- Avoid Accidents
- Improved Working Conditions
- Reduce Fatigue
- Anti-Collision Intelligence

Safety



- Multiple Machines
- Faster Tramming
- Hot Seat Transition
- Remove Disparity between Operators
- Improve Overall Efficiency
- Faster Cycle Times

Productivity

Call us today!
TRYSOME
AUTO-ELECTRICAL ENGINEERING

Delivering Optimal **Uptime!**