

BENEFITS

- Light weight
- Yellow homologated thermoplastic chock
- TUV Certified DIN76051

TECHNICAL FEATURES

MATERIAL: 100% first choice polypropylene
PRODUCTION TECHNOLOGY: Injection moulding


NANY WHEEL CHOCK E36




The E36 wheel chock applies to tyres with a static radius max. of 360 mm and an axle load of 3 tons.

DIMENSIONS

Part No.:	L (mm)	W (mm)	H (mm)	R (mm)	Weight (kg)
T26001561444	332	125	150	355	0.44




NET 46 WHEEL CHOCK G46



The G46 wheel chock applies to tyres with a static radius max. of 460 mm and an axle load of 10 tons.

DIMENSIONS

Part No.:	L (mm)	W (mm)	H (mm)	R (mm)	Weight (kg)
T26001562178	385	193	160	460	0.71




NET 53 WHEEL CHOCK E53



The E53 wheel chock applies to tyres with a static radius max. of 530mm and an axle load of 13 tons.

DIMENSIONS

Part No.:	L (mm)	W (mm)	H (mm)	R (mm)	Weight (kg)
T26001562176	467	198	225	555	1.27



HOST PLASTIC CHOCK HOLDER




DIMENSIONS

Part No.:	L (mm)	W (mm)	H (mm)	R (mm)	Weight (kg)
T26001562179	184	194	128	G46/small	0.45
T26001562177	213	183	137	E53/big	0.44

AVAILABLE FOR E36, G46 & E53

FEATURES & BENEFITS

- High-standard design
- Anti-scratch surface
- Double safety system



This may not be a stock item. Please speak to our sales representative about lead times. Lead times, price and availability can only be determined on receipt of an official quote from our supplier. This can sometimes take up to 3 days.

Gauteng (HO):

T: +27 (0)11 823 5650

North West:

T: +27 (0)14 596 5257

Eastern Cape:

T: +27 (0)81 036 9111

Botswana, Letlhakane:

T: +267 297 8568

KwaZulu Natal:

T: +27 (0)31 303 4129

Mpumalanga:

T: +27 (0)13 692 8132

Free State:

T: +27 (0)63 257 0505

Mozambique:

T: +258 252 20666

Northern Cape:

T: +27 (0)53 723 3415

Western Cape:

T: +27 (0)21 945 1453

Botswana, Jwaneng:

T: +267 588 7617

Zambia:

T: +26 (0)21 222 5338