

GENERATOR SETS FOR PORTABLE AUTONOMOUS POWER!



Part No.: T030012509

DIESEL 15000 TE SILENCE

PORTABLE POWER

Generating Sets Range DIESEL

PRODUCT ADVANTAGES

- Entire group guaranteed 3 years
- KOHLER air-cooled industrial engine
- Very silent
- Sound and shock proof
- Hydrocarbons bulk tank

This genset is quiet and compact and features easy-to-reach components for simplified maintenance. The APM202 control panel displays overspeed, starting failure, oil pressure, battery and temperature.

Range DIESEL

This product features very long run times and long life span for professional applications.



This product meets the Qualigen charter, which aims to ensure a high level of quality and guarantees the safety of users. Qualigen: commitment to safety and quality.

GENERAL SPECIFICATIONS

Range	Diesel
Frequency (Hz)	50 Hz
Max. Power LTP (kW) *	10
Max. Power LTP (kVA)	12.50
Nominal Voltage (V)	400
Number of Phase	Three Phase
Fuel	Fuel
Tank (ℓ)	27
75% Cons. (Brush Script MT /h) *	2.10
75% Autonomy (h) *	12.90
Sound Power Level Guaranteed LwA dB(A)	97
Acoustic Pressure Level @1m in dB(A)	81
Acoustic Pressure Level @7m in dB(A) 67	67

ENGINE SPECIFICATIONS

Engine Brand	KOHLER Diesel
Engine Type	KD425-2
Distribution	Diesel O.H.V.
Start	Electrical
Oil Shutdown	Oui
Displacement (cm ³)	851
Oil Capacity (ℓ)	2.60

ALTERNATOR SPECIFICATIONS

Technology	Collar and brush
AVR Regulation	No
Indication of Protection	IP23
Insulation Class	H

PLUGS AND PANEL DESCRIPTIVE

1 230 V 10/16 Amp socket - circuit breaker + 1 230 V 16 Amp socket - circuit breaker + 1 400 V 16 Amp socket - circuit breaker + hour metre + indicator + APM202

DIMENSIONS AND WEIGHT

Length (cm)	118.30
Width (cm)	67.30
Height (cm)	96
Dry Weight (kg)	275

PACKAGING

Packaging Type	Box
Length (cm)	120
Width (cm)	69
Height (cm)	94
Weight (kg)	278
Pallet Type	
Number of Box by Pallet	0
Pallet Height (cm)	0
Weight of the Packaged Pallet (kg)	0


ACCESSORIES SUPPLIED



User and Maintenance Manual



Battery without Maintenance



Lifting Eye



Hour Metre

OPTIONS



R03B

This set includes a differential switch, an hour metre, the plugs and a thermal circuit breaker.



RSTART2

Remote control in order to start or stop the generating set until a distance of 50 metres (needs the APM202 control panel).



VERS050

Switches over automatically if the mains fails, 40 Amp or 100 Amp 1P or if the mains fails, 25 Amp or 40 Amp 3P (needs the installation of a APM202 control panel). Includes the battery charger.



RKB5

Trolley kit with 1 handle and 2 solid tyres for Diesel 10000 E SILENCE and Diesel 15000 TE SILENCE gensets.



R08E

Lightweight, steered and braked road trailer (GVWR up to 500 kg with registration). Overall dimensions (W x D x H): 2.9 x 1.3 x 1.1 m. uW: 130 kg.



RKDS3

Maintenance kit for KOHLER KD425-2 engine.



Adaptor for Industrial Sockets

ERR: not found in dict valeurs.



RPM

Male plugs for all models made up of : 2 x 16 Amp/230 V, EEC17: 1 x 16 Amp/230 V, 1 x 32 Amp/230 V and 1 x 16 Amp/400V

This may not be a stock item. Please speak to our sales representative about lead times. Lead times, price and availability can only be determined on receipt of an official quote from our supplier. This can sometimes take up to 3 days.

Gauteng (HO):

T: +27 (0)11 823 5650

North West:

T: +27 (0)14 596 5257

Eastern Cape:

T: +27 (0)81 036 9111

Botswana, Letlhakane:

T: +267 297 8568

KwaZulu Natal:

T: +27 (0)31 303 4129

Mpumalanga:

T: +27 (0)13 692 8132

Free State:

T: +27 (0)63 257 0505

Mozambique:

T: +258 252 20666

Northern Cape:

T: +27 (0)53 723 3415

Western Cape:

T: +27 (0)21 945 1453

Botswana, Jwaneng:

T: +267 588 7617

Zambia:

T: +26 (0)21 222 5338