

Rajant BreadCrums®

Powerful Functionality in a Compact Form



Rajant's Kinetic Mesh® network is unlike any other wireless mesh system on the market today, providing fully mobile broadband connectivity that is simple, instantaneous, and fault-tolerant for any application.

The network's power lies in Rajant's wireless BreadCrums: the compact, lightweight, industrial-grade nodes that form this agile, adaptable wireless infrastructure.

BreadCrums have unique capabilities that enable them to perform flawlessly in even the most hard-to-network environments and make them ideal for deployment across ever-moving operations.



Peer-to-Peer Functionality

Every Rajant BreadCrumb can hold multiple simultaneous connections, over multiple frequencies, with other nodes in the mesh, eliminating the need for a controller node while adding network reliability.



Self-Optimise without Intervention

InstaMesh enables the nodes to adapt in real-time to quickly or constantly moving network elements. No connections have to be broken for new ones to be made, providing for resilient mobility.



Deployable as Fixed or Mobile Nodes

Compact, lightweight BreadCrums can be affixed to static equipment or deployed directly on moving assets – so machines and personnel can take connectivity with them wherever they go.



Support Seamlessly Scalability

If new BreadCrums are added, they automatically begin meshing with neighboring nodes and further strengthen the network by providing additional paths to send traffic.



Infused with InstaMesh Intelligence

All BreadCrums have Rajant's patented InstaMesh networking software onboard, which dynamically evaluates and directs traffic via the best available path(s) at any given moment.



Perform in Extreme Conditions

The industrial-strength design of the nodes, coupled with IP67-rated dust-tight and water-tight enclosures for most models, allow them to operate continuously in virtually any environment for years.

BreadCrums can easily integrate with and enhance existing network infrastructure, including third-party satellite, wired, point-to-point wireless, point-to-multipoint wireless, or can be deployed ad hoc to bring connectivity where no communications infrastructure yet exists.

Rajant BreadCrumb Portfolio:

Find the Right Radio for the Right Function



Use the chart below to compare the features and functionality of our wireless BreadCrumb offerings.

	Peregrine	LX5	Hawk
Typical Radio Configuration	Quad 2x2 MIMO transceivers	Dual 2x2 MIMO transceivers plus dual 1x1 SISO transceivers	Dual 2x2 MIMO transceivers
Number of Radios	4	3 or 4	2
Max Antenna Ports	8		64
900 MHz Supported	Pending	Yes	No
2.4 GHz Supported	Yes	Yes	Yes
4.9 GHz Supported	No	No	Pending
5 GHz Supported	Yes	Yes	Yes
10/100/1 000 Ethernet	2	2	2
10/100 Ethernet	0	0	0
# of USB Ports	1	2	1
Enclosure	Aluminium IP67	Aluminium IP67	Aluminium IP67
Input Voltage	20 to 60 Vdc	18 to 48 Vdc	20 to 60 Vdc
Power Consumption (idle/peak)	10 w/34 w	8 w/33 w	10 w/24 w
Operating Temperature (with heater if available)	-40 ° to 80 °C	-40 ° to 80 °C	-40 ° to 80 °C
Ideal Applications	High performance and high throughput. Enhanced security. Military, Mining, Rail, Shipping Ports, Heavy Construction	Industrial Infrastructure. Mining Autonomy, Heavy Construction, Ports, Automation, Tele-Operation	High performance and high throughput. Enhanced security. Military, Mining, Rail, Shipping Ports, Heavy Construction
Max Modulation	256-QAM	64-QAM	256-QAM
Max Channel Size	80 MHz	40 MHz	80 MHz
Maximum Transceivers	4	4	2
MIMO	2 x 2	2 x 2	2 x 2
Combined Data Rate	2.3 Gbps	900 Mbps	1.7 Gbps
User Throughput	Up to 600 Mbps	Up to 80 Mbps	Up to 600 Mbps
Interface Connectors	M12, USB Type A	Squid	M12, USB Type A
Encryption Processing	Hardware Accelerator	Hardware Accelerator	Hardware Accelerator
Radio Type	Up to 802.11 ac	Up to 802.11 ac	Up to 802.11 ac
Dimensions	264.9 x 253.7 x 46.2 mm	197 x 220 x 29 mm	264.9 x 253.7 x 46.2 mm
Weight	2 946 g	1 850 g ± 150 g (weight depends on transceiver configuration)	2 600 g



ME4

ES1

KM3

JR3

DX2

Dual 2x2 MIMO transceivers	Dual 2x2 MIMO transceivers	Dual 2x2 MIMO transceivers	Single 1x1 SISO transceivers	Single 2x2 MIMO transceiver
2	2	2	1	1
4	4	4	1	2
Yes	Pending	Yes	No	No
Yes	Yes	Yes	Yes	Yes
Yes	Pending	No	No	No
Yes	Yes	Yes	Yes	Yes
1	1	1	0	1
1	0	1	1	0
1	1	1	0	1
Aluminium IP67	Plastic IP67	Aluminium DIN rail mount	Plastic, weather resistant	Magnesium, unsealed
8 to 48 Vdc	9 to 30 Vdc	24 to 48 Vdc	9 to 30 Vdc	8 to 60 Vdc
5.5 w/19 w	2.8 w/15 w	5.5 w/19 w	1.8 w/6 w	2.8 w/7.5 w
-40 ° to 80 °C	-40° to 60 °C	-20 ° to 50 °C	-30 ° to 70 °C	-40 ° to 60 °C
Mid-tier. Heavy Equipment, Agriculture, Industrial Security, Ports, Automation, Tele-Operation	Mid-tier, less ruggedised. Energy, Plants, Warehouses, Agriculture, Manufacturing, Commercial, Light Vehicles, Public Safety, Industrial Security	Mid-tier, needs a NEMA IP44 minimum enclosure for outdoor. Energy, Plants, Warehouses, Agriculture, Manufacturing, Commercial, Public Safety, Industrial Security	Edge Device. Agriculture	Smallest node. Drones, Small Robots, Drone Swarming, Public Safety, Industrial Security
64-QAM	64-QAM	64-QAM	64-QAM	64-QAM
40 MHz	40 MHz	40 MHz	40 MHz	40 MHz
2	2	2	1	1
2 x 2	2 x 2	2 x 2	1 x 1	2 x 2
600 Mbps	600 Mbps	600 Mbps	150 Mbps	300 Mbps
Up to 80 Mbps	Up to 70 Mbps	Up to 80 Mbps	Up to 45 Mbps	Up to 140 Mbps
Squid	RJ45, M8	RJ-45, USB Type A	Squid	RJ-45, USB Micro B
Hardware Accelerator	Software	Hardware Accelerator	Software	Software
Up to 802.11 ac	Up to 802.11 ac	Up to 802.11 ac	Up to 802.11 ac	Up to 802.11 ac
189 x 95 x 51 mm	138.735 x 143.154 x 57.15 mm	155 x 149 x 41 mm	177 x 44 x 44 mm	108 x 43 x 40 mm
1162 g ± 100 g (weight depends on transceiver configuration)	1074 g ± 100 g (weight depends on transceiver configuration)	440 g ± 10 g	193 g	123 g ± 10 g

BreadCrumb Benefits:

Network Infrastructure for Today's Interconnected, Mobile World

Rajant BreadCrumb nodes are purpose-built to reliably enable voice, video, and data communications instantly and without fail almost anywhere. They readily form a fully redundant web of meshed connections to deliver more reliability, mobility, and resiliency using less infrastructure than other wireless networking options like Wi-Fi or LTE.

Rajant BreadCrumbs have been proven in the field for two decades to deliver on the promises of:

- **Robust fault tolerance:** no single point of failure & ability to work around interference
- **High bandwidth and low latency:** nodes have hundreds of potential paths to direct traffic
- **Total, 'never-break' mobility:** enables M2M communications, autonomy, and more
- **Cost-effective network scalability:** requires minimal technical resources to manage and expand
- **Military-grade network security:** every node has multiple cryptographic options



Not sure what BreadCrumb is best for your application?

We're ready to help you further assess your network requirements and will recommend the appropriate solution for your needs.

Get in touch today:
Divan.Strydom@trysome.co.za

This may not be a stock item. Please speak to our sales representative about lead times. Lead times, price, and availability can only be determined on receipt of an official quote from our supplier. This can sometimes take up to 3 days.

Gauteng - Jet Park (HQ):

T: +27 (0)11 823 5650

Free State - Bloemfontein:

T: +27 (0)63 257 0505

Eastern Cape - Port Elizabeth:

T: +27 (0)81 036 9111

KwaZulu Natal - Pinetown:

T: +27 (0)31 303 4129

Mpumalanga - Middelburg:

T: +27 (0)13 692 8132

Northern Cape - Kathu:

T: +27 (0)53 723 3415

Northern Cape - Springbok:

T: +27 (0)60 570 8092

North West - Rustenburg:

T: +27 (0)14 596 5257

Western Cape - Cape Town:

T: +27 (0)21 945 1453

Botswana, Gaborone:

T: +267 399 4150

Botswana, Jwaneng:

T: +267 588 7617

Botswana, Letlhakane:

T: +267 297 8568

Mozambique, Tete:

T: +258 252 20666

Zambia, Kitwe:

T: +26 (0)21 222 5338

Follow us...



Call us today!
TRYSOME
AUTO-ELECTRICAL ENGINEERING

trading@trysome.co.za • www.trysome.co.za • PO Box 13677, Witfield 1467