# PRODUCT PROFILE & PROMOTION



Delivering Optimal Uptime!

**ISSUE 83** - AUG/SEP 2025

### **IN THIS ISSUE**

360° Camera System1	1
Alcohol Breathalyser1	2
Alternators	.4
Batteries	.9
Battery Chargers	.7
Beacons	.6

Connectors8-	9
Connector Kits	9
Consumables1	C
Converters	.7
Driving Lights	.6

Interior Lights .....6 Jump Starters.....7 Low-Voltage Disconnects ......7

Pedestrian Detecting System ......11 Rollover Protection System ......10 Safety Lights ......6 Starters.....2-3 Mine-Spec. Products ......4 Work Lights.....5



### fabbro

### 0001416002 STR1047

#### **Bosch-Type KB Starter**

- 24 V
- 9 Tooth
- 5.4 kW
- Short
- 3 Hole Deutz/Man/ Isuzu/ MB



### fabbro

#### T020409209 0120469008 ALT1173

T0104036113

### **Bosch-Type N1 Alternator**

- 24 V
- 55 Amp
- 56 mm Double Foot
- Deutz/KHD/ Liebherr/ Powerstar





### **Deutsch DT Series Large Connector Kit**

- Environmentally Sealed Transportation Connectors
- · Tactile and Audible Assembly Feedback
- Field-Proven Long Service Life
- Engine Compartment Rated
- · Meets Most Harness Design Requirements
- Superior Environmental Seal
- · Low-Cost, High-Reliability Terminals for Data & Signal Transmission
- No Crimper







T440008617 **DT KIT** 





### **TERMS & CONDITIONS OF SALE**



### WARRANTY STATEMENT

Trysome warrants that all products will be covered for manufacturing faults. Trysome's warranty does not, however, extend to rectifiers, regulators, globes, fuses, or diodes.

All products supplied by Trysome are supplied and provided on the condition that we cannot be held responsible in the event that they are used for any other purpose than that specified by the manufacturer. Trysome's warranty, therefore, does not cover misuse, abuse, incorrect fitment, or application.

The customer or purchaser accepts that it is their responsibility to ensure that the product is used in accordance with the manufacturer's instructions.

The commencement date of all warranties is the date of invoice to the purchaser, unless otherwise agreed by Trysome in writing.

> For bulk discounts on premium brands contact: Dawid.Boshoff@trysome.cc

### **SERVICE**

Trysome has its own service department with qualified technicians so that, unlike many wholesalers, we are able to provide you, our Customer, with a complete after-sales service.

#### Note:

- Trysome Auto Electrical Engineering (Pty) Ltd reserves the right to change terms, conditions and specifications shown in this catalogue at any time.
- Some names and part numbers are used for reference purposes only.
- Some of our products are manufactured to order so please allow lead times.
- The information contained herein is deemed to be correct at the time of going to print, but Trysome assumes no liability for typographical errors or omissions.
- Copyright 2025 by Trysome Auto Electrical Engineering (Pty) Ltd. All rights reserved.
- E&OE

Trysome Auto Electrical Engineering (Pty) Ltd is the authorised distributor of the brands it markets.

### **Auto**Tech



### ROTATING EQUIPMENT

T018803604

T014700400

T0104036104

0001241008

4280006170

STR6762

081382305

STR1020

### **STARTERS**

### fabbro T010403696B STR1206 **Bosch-Type Starter** • 12 V • 9 Tooth • 2.3 kW

0001223016

#### **Bosch-Type** JF Starter

- 12 V
- 9 Tooth 2.7 kW

fabbro

- Short
- 3 Hole
- Deutz



fabbro

# Magnetti Marelli-Type

Starter

- 12 V
- 10 Tooth
- 3.0 kW
- MF/JCB (Perkins Engine)



T017915026B

T018919603B

TM000A28901

STR0018

2873K404

fabbro

PMGR

KHD/Deutz/

Bomag/JCB

### T0110419619B 11131781 STR7974



- 12 V
- 10 Tooth
- 3.2 kW
- PLGR
- · Right Hand Open (Front View)

Perkins

### fabbro



- 12 V
- 11 Tooth
- 2.2 kW
- Caterpillar/CASE **New Holland**



## fabbro

### Valeo-Type Starter

- 12 V
- 11 Tooth
- 2.7 kW **PLGR Bobcat**
- Skidsteer



### fabbro

#### Nippon Denso-**Type Starter**

- 24 V
- 10 Tooth
- 7.5 kW OSGR

### (Dry Clutch) Cummins/CASE

#### T0100150002 2280007380 STR6052



## fabbra

### **Bosch-Type Starter**

- 24 V
- 11 Tooth
- 5.5 kW PLGR
- · Including IMS
- Powerstar 26/280



## fabbro

## Delco-Type 39MT

- Starter 24 V
- 12 Tooth 9.0 kW
- Cummins/
- Caterpillar





### **STARTERS**



## fabbro

### T011919602B

#### 03517020682 STR9861

### Sawafuji-Type Starter

- 24 V
- 12 Tooth
- 11 kW
- **OSGR KOM** PC800



# WAI

High-Performance Rotating Equipment for a **Dynamic Aftermarket!** 





12 Tooth

Direct Drive

• 8.0 kW

#### **Delco-Type** 39MT Starter

- 24 V
- 11 Tooth
- 8.3 kW · Rotatable Flange







T011003687B









### **42MT Starter**

- 24 V
- 11 Tooth
- 8.0 kW
- · Direct Drive
- CAT/Cummins/ERF






















Brushless

Air Cooled



T020009202B

2871A303

### **ALTERNATORS**

### fabbro

## Magneti Marelli-Type

- Alternator • 12 V
- 85 Amp
- LH CAT/Manitou



T022809246B

### fabbro

#### Mitsubishi-Type **Alternator**

- 24 V
- 50 Amp • 2 Pin (L-S)
- Hitachi EX850/ Isuzu Excavator



### fabbro

### Iskra/Letrika-Type

- Alternator • 24 V
- 80 Amp
- Double 56 mm Foot
- Deutz/Normet



T027909211B

IA1031

### fabbro

### Nippon Denso-Type Alternator

- 24 V
- 95 Amp
- · CAT D10R



### fabbro

### Mando-Type J1 Alternator

- 24 V
- 150 Amp Mercedes-Benz HD10LPB



T0204092291

# MITSUBISHI ELECTRIC

#### **Alternator**

- 24 V
- 50 Amp
- · Triple Pulley
- 2 Pin (S-L)
- Compatible with Hitachi/Isuzu 6WGI/ John Deere





#### **30SI Alternator**

- 24 V
- 100 Amp J180 Mount
- No Pulley
- CAT/Cummins





### 36SI Alternator

- 24 V
- 105 Amp J180 Mount
- CAT/Cummins Komatsu/ Volvo Industrial **Applications**





#### **40SI Alternator**

- 24 V
- 160 Amp · J180 Mount
- International Truck Engines/ Volvo/CAT/ Freightliner



Working in hazardous environments requires safety to be the highest priority. Our products help increase safety across the entire automotive value chain.











**VLCOECVU**®







### **WORK LIGHTS**













### **GLOBES**

lmage	Part No.	OE No.	Electrolog No.	Brand	Description	Watts
	TGLOB1034F	5229	GLB0380	Flösser	12 V, DCDF BAY15d	21/5 w
	T211801908F	3324	GLH0034	Flösser	24 V, H3, PK22s	70 w
4	T211813342F	825543	GLH4504	Flösser	24 V, H4, P43T	75/70 w
	T64215F	2470	GLH7001	Flösser	24 V, H7, PX26d, 2-Pin, 34 mm Base	70 w



### **BEACONS**

### T720019836 **LED Beacon**

- 10 30 V
- 24 w
- · Amber Lens • 11 Flash Patterns
- · Magnetic Mount and Cigarette Lighter Plug
- · Operating Temperature: -40 °C to +65 °C

116 x 130 mm

### **SAFETY LIGHTS**

### **Red Zone LED Forklift Light**

• 9 - 64 V

- 18 w
- · Pedestrian Safety

186 x 88 x 61 mm





T720019729

### **DRIVING LIGHTS**

T310003807/ T310019783

IP68

**E9** 

### **Sentinel Elite Driving Lights**

### **High Beam**

- 10 32 V
- 116 w or 145w in Boost Mode
- 5 000 k
- With Positioning Light
- · Slim Mount
- 24 or 20 LEDs
- 10 000+ or 15 000+ Lumens in Boost Mode
- 1.5 or 2.4 kg

7-Inch LED

• 16 x 5 w

• 6 000 K

**Driving Light** 

10 - 30 Vdc

• 9 600 Lumens

ECE Approved

187 x 192 x 78 mm

· Operating Voltage:





T960-509/10



( NORDICLIGHTS **Sculptor 2** 

517 x 71 x 39 mm

### **High and Low Beam**

• 12 - 24 V

- · Left or Right (sold individually)
- Right-hand Traffic
- · Built-in Deutsch
- ECE
- Quake Dampening
- · Rear Mount

251 x 157 x 151 mm

### **INTERIOR LIGHTS**

ultra low-profile design.





### **JUMP STARTERS**

#### NOCO T260016904 Since 1914 GB251-GB251+ Boost Max Ultra Safe Lithium Jump Starter • 24 V Amp · 133 Wh Lithium Ion • Starts up almost every type of vehicle and equipment, including semi-trucks (up to class 8), 24V motor homes, buses, mining, agricultural, and NOCO BOOST'MAX" ( construction. · It's not just a lithium jump starter but also a 0 portable power bank for recharging smart phones, tablets, and other USB devices. • Recharge time - 8.5 hours • 6.17 kg





### **BATTERY CHARGERS**

#### NOCO **Since 1914**

#### T120016956 **GENIUSPRO50**

Amp

IP20

### **Genius PRO50 Battery Charger**

- · Precision Charging that Eliminates Overcharging
- Fully Automatic Professional Smart Charger
- 6 V, 12 V, and 24 V Automotive Charging
- 1.51 kg







### T286512832

ICI-24 144

#### DC-DC Intelligent **Battery Charger**

- 24 24 V
- 144 w
- Isolated
- 600 g

These intelligent DC-DC battery chargers operate a fourstage charging cycle.



170 x 87 x 42 mm

### **CONVERTERS**

### LOW-VOLTAGE DISCONNECTS







**CONNECTORS** 





**TE Connectivity Connectors** offer different shapes, latching mechanisms, mounting styles, and materials to meet diverse application requirements and offer accessories to further expand the series' flexibility.



























**CONNECTORS Built to CAT Spec.** 

lmage	Part No.	OE No.	Description	Size	Colour
	T21001631693	776427-1	2-Position Ampseal 16 - Assembly Plug Single Row	1.58 mm	Black/Red
	T21001631694	776429-1	3-Position Ampseal 16 - Assembly Plug Single Row	1.58 mm	Black/Red
	T21001631695	776433-1	6-Position Ampseal 16 - Assembly Plug Dual Row	1.58 mm	Black/Red
	T21001631696	1717672-1	2-Position Ampseal 16 - Assembly Cap Reverse Mount	1.58 mm	Black/Grey
	T21001631697	1717673-1	3-Position Ampseal 16 - Assembly Cap Reverse Mount	1.58 mm	Black/Red
	T21001631698	1717674-1	4-Position Ampseal 16 - Assembly Cap Reverse Mount	1.58 mm	Black/Red
	T21001631699	1717675-1	16-Position Ampseal 16 - Assembly Cap Reverse Mount	1.58 mm	Black/Red

**KITS** 



#### VISIT OUR WEBSITE or a full contents list

#### **Deutsch Connector Kit**

This 320-piece Automotive Electrical Connector Kit is tailored for the Deutsch DT Series, offering dependable and long-lasting connections for a variety of automotive uses. The kit includes a variety of receptacles, plugs, wedgelocks, pins, and sockets providing a complete solution for your wiring needs. Excludes crimper.



# Sealed Maintenance-Free Batteries Maximum power, every time! Trysome boasts a broad auto-electrical product range which includes the Trylec, TrylecHD, and TyrlecXHD Premium Battery Range.

TRYLEC **BLACK SERIES** 









### **CONSUMABLES**

### **SPANJAARD**

T2600156110298

### Windscreen Cleaner

500 ml



### **SPANJAARD**

**Tyre Fix Sealant** 

• 340 ml



#### T2600156110296 **SPANJAARD**

### Tyre Fix Sealant

- 4x4
- 600 ml



### **SPANJAARD**

### **Air-Conditioner Cleaner**

- Aerosol Sprav
- 300 ml



#### T120012715B **SPANJAARD**

#### Silicone Paste

- Tube
- 100 g



### **SPANJAARD**

Radiator Sealer & Conditioner

• 375 ml



T26001562181

### **=** Spanjaard

#### T26001563454B

### **Cold Zinc Galvanising Spray**

· Aerosol Spray 400 ml



### **SPANJAARD**

### **HTS Silicone Grease**

• Tin

• 500 g



### **SPANJAARD**

### **Penetrating Aero Spray**

• 350 ml





Using the patented HALO™ Rollover Occupant Protection System on your fleet of vehicles will ensure that you are protecting your occupants with the best-possible system and significantly reduce the likelihood of injury.

Named HALO™, the structure is a High Attenuation Load Offset device. The HALO™ design maximises the vehicle's geometry to minimise and evenly distribute the impact forces of a rollover event over the entire vehicle body structure, preventing a concentrated load in any one place. When attached to a production vehicle roof, along with internal reinforcements, HALO™ reduces the speed and amount of crush in the roof structure when the vehicle experiences a rollover crash.

### Safety Benefits:

- **Stronger Roof Structure –** The HALO™ Rollover Protection System increases the roof strength to 6x the vehicle weight.
- More Robust Side Structure The HALO™ Rollover Protection System's steel reinforcement increases sideimpact protection.
- Eliminates Internal Hazards NO internal steel bars to cause head or tripping injuries.
- Certified Installation Service Only Certified Licensed Installers are appointed, ensuring a safe HALO™ fitment.

These safety advantages will ensure your assets keep delivering for maximum uptime!



# **OPTICS**




### **Q2Smart Intelligent Pedestrian & Vehicle Detecting** and Warning Camera.

This innovative system adopts deep-learning technology to accurately detect pedestrians and vehicles, ensuring realtime safety for drivers.

#### **Features**

- Realtime Detection Detect pedestrians and vehicles (including cyclists and electric bikers) within 8m/10m in front of the vehicle.
- Wide Viewing Angle With a 170°/200° horizontal viewing angle, it eliminates blind spots and provides a better view, helping avoid accidents.
- Visual & Audio Alarms The camera works with a Q2Smart HD monitor to give realtime alarms, ensuring drivers are always aware of potential risks.
- Durable & Reliable IP69K waterproof, ISO16750-3 anti-vibration, and built to withstand the toughest environments.
- Easy Setup With USB2.0 support and the ability to configure via mobile or USB flash drive, setup is hassle-free.



Perfect for large vehicles where visibility is critical.





### Why Choose Our 360° Camera System?

- Seamless 360° Coverage: Enjoy a bird's-eye view with no blind spots for safer driving.
- Flexible Viewing: Switch between 3D/2D views for complete control of your environment.
- Al-Powered Pedestrian Detection: Detect pedestrians up to 10 metres away with our external AI camera system.
- Night Vision Capability: See clearly even in low light conditions, with
- Rugged Durability: Waterproof, dustproof, and built to withstand harsh conditions.






### **Prevent Drunk Driving Before It Starts. Ensure Safe Driving with ALCOSCAN.**

This advanced Breath Alcohol Ignition Interlock Device (BAIID) prevents a vehicle from starting if alcohol is detected on the driver's breath. Ideal for both personal and fleet vehicles, the ALX3000 ensures every driver is fit to drive.

### **How it Works**

A driver must pass a breathalyser test using the ALCOSCAN ALX3000 handset before the engine can start. If alcohol is detected above the legal limit, the ignition is disabled.



### **Handset Features**

- Alcohol Sensor: Fuel Cell Sensor to detect alcohol in breath
- **Temperature Sensor:** Temperature detection, environment, breath, etc.
- Flow Sensor: Detects breath pressure & volume of exhaled air
- Altitude Sensors: Adjustment of breathing deviation according to altitude
- Breath sampling tube: The structure that accepts breathing under certain conditions
- **Chamber:** Maintains exhaled breath conditions (temperature & humidity)
- Pump: Structure that accepts a certain amount of breathing time
- MCU: Management of measurement algorithm
- Memory: Stores the measured reference value and the measured result value
- **Display:** Displays the status and measurement result values
- Buzzer: Indicates the status and measurement result as sound

### **Control Box Features**

- Relay Control: Disables ignition on failed test
- MCU & Timer: Manage test logic and timing
- Data Memory: Stores up to 100 000 event logs
- Communication IC: Sends data to PC or server
- Power & I/O Circuit: Monitors and interfaces with vehicle systems

Eastern Cape - Port Elizabeth T: +27 (0)82 450 6596

Free State - Bloemfontein T: +27 (0)63 257 0505

Gauteng - Bedfordview (FleetTech) Mpumalanga - Middelburg T: +27 (0)10 329 0932

Gauteng - Jet Park (HQ) **T:** +27 (0)11 823 5650

KwaZulu Natal - Pinetown T: +27 (0)31 303 4129

T: +27 (0)13 692 8132

Northern Cape - Kathu T: +27 (0)53 723 3415

North West - Rustenburg T: +27 (0)14 596 5257

Western Cape - Cape Town T: +27 (0)21 945 1453

Rotswana - Gahorone T: +267 399 4150

Mozambique - Tete T: +258 252 20666

Zambia - Kitwe T: +26 (0)21 222 5338





Delivering Optimal Uptime!

trading@trysome.cc - www.trysome.co.za - PO Box 13677, Witfield 1467